



Strong and flexible wheel suspension with four large pivoting wheels, staggered to ensure optimal functioning and minimal wear on the machine.



The top link attachment is equipped with two holes, and an oblong hole for working in lightly undulating terrain.



Strong and flexible shield between the rotors ensures that no material is flung from one rotor to the other, thereby ensuring an even and uniform swath.



The machine's compact transport dimensions make it easy to go through narrow passages and work in small fields.

Technical data:	BF-6300
Working width	6.30 m / 248"
Transport width	3.0 m / 118"
Raker arms per rotor	9 pcs.
Double springs per rake arm	3 pcs.
Rotor diameter	3.10 m / 122"
Number of wheels per rotor	4 (16.5 x 6.5-8/6 ply)
Number of hydraulic outlets	1 double-acting
Tractor output	60 kW
3-point suspension	Category II
PTO r.p.m.	400-540
Shield	Standard
PTO axle	Standard
Transport chain	Standard
Weight	1160 kg / 2557 Lbs

Dealer:

Importer:

Fransgård BF - rotary hay rake



Made in Denmark

- Strong mounted rotary hay rake with two rotors
- Hydraulic folding for transport
- Folding safety guard ensures narrow transport width (3.0 m)
- Transport width 3.0 m
- Working width of 6.30 m
- 9 arms with 3 double tines on each rotor
- 4 large wheels, staggered under each rotor
- Separate continuous height adjustment on each rotor
- 3-point mounted unit which is very convenient for working in tight areas



Fransgård

Fransgård Maskinfabrik A/S
9640 Farsø, Denmark www.fransgard.dk