

Fransgård SV – Swath wilter



SV-250-09 SV-250-09SE

Strong and solid swath wilter. The swath wilter comes with two big swath doors. SV-250-09 is built with a horizontal rotor with 72 double pick up tines. It picks up the material without stone or soil getting into the crop. The Swath wilter conditions evenly and forms a smooth airy swath. The swath wilter is the ideal machine for straw and grass.

Fransgård



The swath can be moved to either side to allow the ground to dry underneath. There is less ground compaction, as the following machines do not drive in the wheel tracks from previous passes.



The large fixed wheels ensure a steady and gentle operation, and the highly flexible suspension ensures that the machine follows the terrain. The suspension is automatically locked when the machine is raised in the lift.



The large adjustable guards will form an ideal fast drying swath. During transport, wheels can be placed upwards to lower transport width.



The side-conveyor mechanism can be raised hydraulically, enabling positioning the material, in full width, behind the machine. Swath deflectors (optional) can also be mounted to facilitate material placement.



72 double tines pick up and condition the crop effectively, resulting in a well formed, loose, airy swath. These robust duty tines were purpose built for this machine and have been proven in heavy wet material over many years.



The hydraulic side-conveyor can be operated in both directions and can be adjusted to three horizontal positions according to the material density. The high clearance ensures that the material exits the machine efficiently.

Technical data	SV-250-09	SV-250-09SE
Working width	2,5 m / 8.2 ft	2,5 m / 8.2 ft
Transport width	3,0 m / 9.8 ft	3,3 m / 10.8 ft
Working speed	8-15 km/t / 5-10 mph	8-15 km/t / 5-10 mph
Capacity	2,5-3,9 ha/hr 6,2-9,6 acres/hr	2,5-3,9 ha/hr 6,2-9,6 acres/hr
Power requirement	80 hk / 60 KW	80 hk / 60 KW
Rotor diameter	80 cm / 31,5 in	80 cm / 31,5 in
No of double tines	72 pcs	72 pcs
Tire dimensions	16,5 x 6,5-8 / 6 ply	18,5 x 8 / 6 ply
No. of XPB-belt	4 pcs	4 pcs
PTO	540 rpm	540 rpm
Weight	680 kg / 1.500 lbs	850 kg / 1.874 lbs

Optional – very special conditions



Chain drive

Importer:

Dealer:

Manufactured by:

Fransgård Maskinfabrik A/S
 Fredbjergvej 132, DK-9640 Farsø
 Tlf. +45 98 63 21 22
 www.fransgard.dk